
Bolted bonnet, inside screw with indicator, non-rising stem.

Fig. 10FCHI

• Bronze trim







Materials

Par	ts	Material	JIS Spec.		
Body		Cast Iron	FC300		
Bonnet		Cast Iron	FC300		
Stem		Forged Brass	C3771BE		
Disc	11/2	Bronze	CAC406		
DISC	2 to 12	Cast Iron	FC300		
Disc seat ri	ng	Bronze	CAC406		
Body seat r	ing	Bronze	CAC406		
Gland		Ductile Iron	FCD-S		
Gland pack	ing	Asbestos-free			
Gasket		Asbestos-free			
Gland bolt/	nut	Carbon Steel			
Bonnet bol	t/nut	Carbpn Steel			
Bonnet bus	hing	Bronze	CAC406		
Hand whee	el	Cast Iron	FC250		

 $120\,^{\circ}\text{C}$ Non-shock water 1.0 MPa, $120\,^{\circ}\text{C}$ Water, oil, air 0.9 MPa Saturated steam 0.7 MPa

Dimensions

Differisions												
	Valve Size		11/2	2	21/2	3	4		6	8	10	12
V	Valve Size		40	50	65	80	100	125	150	200	250	300
1	. Face-to-face		140	146	159	165	171	190	210	241	273	305
	Height		210	250	285	350	400	460	515	635	760	870
D	Handwheel Diar	meter	140	140	160	160	180	225	225	300	350	350