



**Precision Plumbing Products**  
*"Specify with Confidence - Install with Pride"*

**LEAD FREE**

**WATER HAMMER ARRESTORS  
 STAINLESS STEEL #316 FLANGED**

www.pppinc.net



**40 Years  
 of outstanding performance**

**Adaptable to your individual needs:**

PPP Stainless Steel Hammer Arrestors are available for all types of fluid systems - water, deionized and triple distilled water, chemicals and petroleum products.

Normal operating pressure for Flanged Arrestors: 35 to 500 PSIG. Spike pressure not to exceed 720 PSIG. Manufacturing lead time: 3-5 weeks.

**PROJECT SUBMITTAL**

Project: \_\_\_\_\_

Contractor: \_\_\_\_\_

Engineer: \_\_\_\_\_

Date Submitted: \_\_\_\_\_

Prepared By: \_\_\_\_\_

**FLANGED ARRESTORS**

PART NUMBER	B OAL	FLANGE SIZE	NITROGEN PRELOAD PSI
SS-3000316FLG	16"	3" - Class 300	40
SS-4000316FLG	19"	4" - Class 300	40
SS-5000316FLG	31"	5" - Class 300	40
SS-6000316FLG	34"	6" - Class 300	40
SS-8000316FLG	39"	8" - Class 300	50

SIZED IN ACCORDANCE WITH SERVICE PIPE DIMENSION

**Finished to your Specifications:**

When ordering, the expected mean spike pressure must be specified as well as the chemical make-up of the fluid in the system and the maximum temperature. Arrestors may be charged at the factory with either air or dry nitrogen per your specification. If arrestors are to be used in systems pumping volatile fluids it is mandatory that they be charged with dry nitrogen.

U.S. Patent No.3,633,62



**JL Industries, inc.**

**Precision Plumbing Products**

Division of JL Industries, Inc.  
 802 SE 199th Avenue  
 Portland, Oregon 97233  
 T (503) 256-4010  
 F (503) 253-8165  
 www.pppinc.net

